ACCESS CONTROL MANAGER[™] 6 PROFESSIONAL

Access Control Manager (ACM) Professional is a web-based, access control network appliance designed for small to medium-sized installations, with up to 32 readers. Intuitive and easy to use, the ACMTM Professional System simplifies access control with a cost-effective, all-in-one appliance.

Unlike legacy, client/server-based access control systems, Access Control Manager Professional is accessible anytime, anywhere from any device that has a web browser, including Firefox, Safari, Chrome™, or Edge. Manage facility access privileges quickly and easily from any location without being tied to a dedicated client workstation or paying for individual software licenses per user.



FEATURES



OPEN ARCHITECTURE

Leverages open field hardware investments.



TURNKEY SOLUTION

All-in-one applicance pre-installed with Access Control Manager software from Motorola Solutions.



SCALABILITY

Desktop machine offers an ideal starting point for smaller businesses with the flexibility to expand as needs change.



COST-EFFECTIVE

Provides smaller businesses with powerful features at a lower cost of ownership.



SMALL FORM FACTOR

Small footprint with powerful performance installs into compact spaces with limited power consumption requirements.



EASY INTEGRATION WITH EXISTING SYSTEMS

Seamless integration with existing IT, logistical and physical security systems.



SPECIFICATIONS

SYSTEM				
Processor	Intel® Pentium® Gold G5400 (2 Cores/4	Intel® Pentium® Gold G5400 (2 Cores/4MB/4T/3.7GHz/65W)		
Memory	4GB (1X4GB) 2666MHz DDR4 UDIMM Non-ECC			
Card Readers	Up to 32			
Inputs	512			
Outputs	512			
Max. Identities	75,000	75,000		
Max. Controllers	1,024	1,024		
Max. Simultaneous Operators	10	10		
Max. Stored Events	75,000,000	75,000,000		
Hard Disk Drive Configuration	500GB 3.5inch Serial ATA (7,200 Rpm) H	500GB 3.5inch Serial ATA (7,200 Rpm) Hard Drive		
Network Interface	Intel 1GB PCIE network card for Small Form Factor			
MECHANICAL				
Form Factor	Small Form Factor	Small Form Factor		
Dimensions (HxWxD)	29 cm × 9.26 cm × 29.2 cm; 11.42" × 3.65	29 cm × 9.26 cm × 29.2 cm; 11.42" × 3.65" × 11.50"		
Weight	6.86 kg (15.09 lbs)	6.86 kg (15.09 lbs)		
ELECTRICAL				
Power Input	100 to 240 VAC, 50/60 Hz, 4.4A	100 to 240 VAC, 50/60 Hz, 4.4A		
Power Supply	Single non-redundant	Single non-redundant		
Power Consumption	300 W	300 W		
ENVIRONMENTAL				
Operating Temperature	0° to 45° C (32° to 113° F)	0° to 45° C (32° to 113° F)		
Storage Temperature	-40° to 65° C (-40° to 149° F)			
Humidity	20 - 80% Relative humidity (non-condens	20 - 80% Relative humidity (non-condensing)		
Operating Vibration	0.26GRMS	0.26GRMS		
Storage Vibration	2.20GRMS	2.20GRMS		
Operating Shock	40G	40G		
Storage Shock	105G			
Operating Altitude	G1 or lower as defined by ANSI/ISA-S7	G1 or lower as defined by ANSI/ISA-S71.04-1985		
Storage Altitude	G1 or lower as defined by ANSI/ISA-S7	G1 or lower as defined by ANSI/ISA-S71.04-1985		
CERTIFICATIONS				
ENERGY STAR	CEL	CCECP	EPEAT	
RoHS	NFPA 99:2012	EMC Class B		
	l .	<u> </u>	I .	

SUPPORTED ACCESS CONTROL SOLUTIONS	SUPPORTED VIDEO INTEGRATION SOLUTIONS
HID® VertX EVO™ HID Global® HID PivCLASS® Mercury Security ASSA ABLOY Allegion Farpointe Data® EasyLobby® by HID LifeSafety Power®	Avigilon Control Center TM Pelco VideoXpert® Exacq Technologies by Tyco Security Milestone Systems IndigoVision® Control Center Compass Decision Management System TM
ViRDI Simons Voss Salto Elmdene	

ORDERING INFORMATION

ORDERING INFORMATION		
AC-APP-16R-PRO-6-P	Access Control Professional Appliance with 16 Readers	
AC-APP-32R-PRO-6-P	Access Control Professional Appliance with 32 Readers	
AC-SW-16RCU-6-P	16 Reader software add-on	
AC-APP-PRO-WARR-EXTEND-1YR	1 Year Extended Warranty for Access Control Manager Professional Appliance	
AC-APP-PRO-WARR-EXTEND-2YR	2 Year Extended Warranty for Access Control Manager Professional Appliance	

SUPPORT

Learn more and find additional documentation at <u>avigilon.com</u> or email <u>sales@avigilon.com</u> for specific product support.



Feb 2022 | Rev 7

MOTOROLA, MOTO, MOTOROLA SOLUTIONS, and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © Motorola Solutions, Inc. All rights reserved. AVIGILON, the AVIGILON logo, ACCESS CONTROL MANAGER, ACM and AVIGILON CONTROL CENTER are trademarks of Avigilon Corporation. The absence of the symbols mand in proximity to each trademark in this document or at all is not a disclaimer of ownership of the related trademark. All other trademarks are the property of their respective owners.